

BOO FOR TENDER

**NAME OF WORK:-LAYING RCC FLAT ROOF FOR BANGALORE
MANAGEMENT ASSOCIATION OFFICE BUILDING AT
ELECTRONIC CITY BEGUR HOBLI, BANGLAORE SOUTH TALUK**

| SI No | Description | Unit | Qty |
|---|--|------|--------|
| <u>CENTERING FOR COLUMNS</u> | | | |
| 1 | KSRB 4-6.5 : Providing and removing centering, shuttering, strutting, propping etc., for columns, pillars, piers, abutments, post and struts, square / rectangular / polygon in plan including cost of all materials, labour complete as per specification. | Sqm | 111.79 |
| <u>CENTERING FOR ROOF SLAB</u> | | | |
| 2 | KSRB 4-6.2 : Providing and removing centering, shuttering, strutting, propping etc., and removal of form work for flat surface such as suspended floors, roofs, landings, balconies and likes, thickness upto 200 mm including cost of all materials, labour complete as per specifications. | Sqm | 362.82 |
| <u>CENTERING FOR EDGES</u> | | | |
| 3 | KSRB 4-6.9 :Providing and removing centering, shuttering, strutting, propping etc., for edges of slabs and breaks in floor, cills, plinth including cost of all materials, labour complete as per specification. | Sqm | 15.70 |
| <u>M-25 CONCRETE FOR ROOF SLAB</u> | | | |
| 4 | KSRB 4.2.7 : Providing and laying in position reinforced cement concrete of design mix M25 with OPC cement @ 340kgs, with 20mm and down size graded granite metal coarse aggregates @0.70cum and fine aggregates @ 0.47cum, with superplasticiser @3lts conforming to IS9103-1999 Reaffirmed-2008, machine mixed, concrete laid in layers not exceeding 15 cms thick, vibrated for R.C.C. beams, columns of all sizes in foundation plinth and superstructure ground floor level for roof slabs, staircase, lintels, columns, including cost of all materials, labour, HOM of machinery, curing, complete as per specifications. | Cum | 90.45 |

| Sl No | Description | Unit | Qty |
|-------|-------------|------|-----|
|-------|-------------|------|-----|

STEEL

| | | | |
|---|---|-------|---------|
| 5 | KSRB 4.9.2 : Providing T.M.T steel reinforcement for R.C.C work including straightening, cutting, bending, hooking, placing in position, lapping and / or welding wherever required, tying with binding wire and anchoring to the adjoining members wherever necessary complete as per design (laps, hooks and wastage shall not be measured and paid) cost of materials, labour, HOM of machinery complete as per specifications. TMT Bars Fe-500. | Kgs., | 9045.00 |
|---|---|-------|---------|